


■Features

- Super Flux Output
- Water Clear Type
- Low Thermal resistance

■Applications

- Automotive Dashboard Lighting
- Traffic Signal Lamp
- Other Exterior Lighting

■Outline Dimension




■Absolute Maximum Rating

(Ta=25 °C)

Item	Symbol	Value	Unit
DC Forward Current	I_F	30	mA
Pulse Forward Current*	I_{FP}	100	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	120	mW
Operating Temperature	T_{opr}	-30 ~ +85	
Storage Temperature	T_{stg}	-40 ~ +100	
Lead Soldering Temperature	T_{sol}	260 /5sec	-

*Pulse width Max.10ms Duty ratio max 1/10

■Directivity



■Electrical -Optical Characteristics

(Ta=25 °C)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
DC Forward Voltage	V_F	$I_F=20mA$	2.8	3.3	3.8	V
DC Reverse Current	I_R	$V_R=5V$	-	-	10	μA
Luminous Intensity	I_v	$I_F=20mA$	1500	2000	-	mcd
Chromaticity Coordinate*	x	$I_F=20mA$	0.42	0.45	0.49	
	y	$I_F=20mA$	0.40	0.43	0.47	
50% Power Angle	$2\theta_{1/2}$	$I_F=20mA$	-	120	-	deg

*Please refer to CIE 1931 chromaticity diagram.