REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 11/05/08	~	





N=No. of contacts/2



NOTES:

1. SPECIFICATIONS
   - . Current Rating: 1A
   - . Insulation Resistance: 500MΩ Min
   - . Dielectric Withstanding: 300V AC
   - . Contact Resistance: 30mΩ Max
   - . Operating Temperature: −20°C to+70°C
2. PART NUMBER: DS1065−05
3. PRODUCT NUMBER CODE:

DS1065−05 − X X X X X

- MOUNTING TYPE
  S:SMT TYPE
- HOUSING COLOR
  B:BLACK
- CONTACT PLATING
  8: FULL GOLD FLASH
- CONNECTOR TYPE
  S:SOCKET
- No.OF CONTACTS
  2*1−2*40



RECOMMEND PCB LAYOUT(TOLERANCE ±0.05)

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C−DS1065−05−XXXXX		

PROJECTION		TITLE	FEMALE HEADER PITCH 1.27mm S.M.T TYPE
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1065−05