



GLASS PASSIVATED SINGLE-OHASE BPIDGE RECTIFIER

GBPC50005 THRU GBPC5010


VOLTAGE RANGE	50 to 1000 Volts
CURRENT	50.0 Amperes

FEATURES

- Plastic package has UL flammability classification 94V-0
- Integrally molded heatsink provides very low thermal resistance for maximum heat dissipation
- High forward surge capacity
- Glass passivated chip junction
- High isolation voltage from case to lugs
- High temperature soldering guaranteed:
260°C/10 seconds,

MECHANICAL DATA

- Case: Epoxy, Molded Plastic with integrally mounted heatsink
- Terminals: Plated 0.25" (6.35mm) lug
- Polarity: Polarity symbols market on case
- Mounting: Thru hole for #10 screw, 20 in-lbs Torque max.
See Note 3
- Weight: 0.62 ounce, 17.5 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

		SYMBOLS	GBPC 50005	GBPC 5001	GBPC 5002	GBPC 5004	GBPC 5006	GBPC 5008	GBPC 5010	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage		V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage		V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current At T _C =55°C (SEE FIG.1)		I _(AV)	50							Amps
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)		I _{FSM}	500							Amps
Rating for Fusing (t<8.3ms)		I ² t	1037							A ² s
Maximum Instantaneous Forward Voltage drop Per Bridge element 25.0A		V _F	1.1							Volts
Maximum DC Reverse Current at rated DC blocking Voltage per element	T _A = 25°C	I _R	5.0							μA
	T _A = 125°C		1.0							
Isolation Voltage from case to lug		V _{ISO}	2500							Volts
Typical Thermal Resistance (Note 1 and 2)		R _{ΘJC}	1.6							°C/W
Operating Junction Temperature		T _J	(-55 to +150)							°C
Storage Temperature Range		T _{STG}	(-55 to +150)							°C

- Notes:**
1. Unit mounted on 9" x 3.5" x 4.6" (23cm x 9cm x 11.8cm) AL Plate.
 2. Bolt down on heat-sink with silicon thermal compound between bridge and mounting surface for maximum heat transfer efficiency with #10 screw



GLASS PASSIVATED SINGLE-OHASE BPIDGE RECTIFIER

GBPC50005 THRU GBPC5010

VOLTAGE RANGE 50 to 1000 Volts
CURRENT 50.0 Amperes

RATINGS AND CHARACTERISTICS CURVES GBPC50005 THRU GBPC5010

FIG. 1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG. 3 - TYPICAL FORWARD CHARACTERISTICS PER BRIDGE ELEMENT




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS PER BRIDGE ELEMENT




FIG. 5 - MAXIMUM POWER DISSIPATION

