ASEMI ELECTRONIC CO.,LTD

KBP2005-KBP210


SINGLE PHASE 2.0 AMPS. GLASS PASSIVATED BRIDGE RECTIFIERS

FEATURES

- UL Recognized File # E-230084
- Ideal for printed circuit board
- Reliable low cost construction technique results in inexpensive product
- High temperature soldering guaranteed: 250°C/10 seconds at 5 lbs.(2.3kg) tension
- Small size,simple installation Leads solderable per MIL-STD-202, Method 208

Voltage Range
50 to 1000 Volts
Current
2.0 Amperes

KBP



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

Type Number		KBP 2005	KBP 201	KBP 202	KBP 204	KBP 206	KBP 208	KBP 210	UNITS
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @T_A = 50°C	$I_{F(AV)}$	2.0							A
Peak Forward Surge Current 8.3 ms Single Half Sine-wave Superimposed on Rated load (JEDEC method)	I_{FSM}	60							A
Maximum Instantaneous Forward Voltage Drop Per leg @ 2A	V_F	1.1							V
Maximun DC Reverse Current @ T_A = 25°C at Rated DC Blocking Voltage @ T_A = 125°C	I_R	10 500							uA uA
Operating Temperature Range	T_J	-55 to + 150							°C
Storage Temperature Range	T_{STG}	-55 to + 150							°C

RATING AND CHARACTERISTIC CURVES
KBP2005 THRU KBP210

FIG.1- MAXIMUN NON-REPETITIVE FORWARD
SURGE CURRENT PER BRIDGE ELEMENT




FIG.2-MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD
CHARACTERISTICS PER BRIDGE ELEMENT




FIG.4- TYPICAL REVERSE CHARACTERISTICS
PER BRIDGE ELEMENT

