

产 品 规 格 书

Product specifications book

样单编号: Kind of single No.:

参 数 Parameters 项 目 Item	型 号 Type	规 格 Specification	容量误差: +20% -20% Error capacity: +20%-20%	温度范围: Temperature Range : +105℃ -40℃
		22UF400V		
外型尺寸 Dimensions (mm)	直径 D13.0+0.5 高度 L21.0+1.0 脚距 F5.0+0.5 脚径 d0.6+0.1 Diameter D13.0 +0.5 highly L21.0 +1.0 pitch the foot diameter d0.6 +0.1 F5.0 +0.5			
性 能 Performance	电容量 C: 17.6-26.4uF 损耗 DF: 20.0% (Max) 漏电 I: 264.0uA(1 分钟) The loss of the electric capacity C :17.6-26.4uF DF: 20.0% (Max) leakage I: 264.0uA (1 minute)			
贮存试验 Storage Test	(105℃ 1000 小时。试验后, 施加额定电压 30 分钟, 于 24 小时至 48 小时之间测试) (105 ° C for 1000 hours after the test, the rated voltage is applied for 30 minutes, the test at between 24-48 hours)		容量变化 ≤ 初始测量值的 ± 20% 损耗值 ≤ 规定值的 ± 200% 漏电流 ≤ 规定值的 ± 200% Capacitance change ≤ ± 20% of the initial measured value Loss value ≤ predetermined value ± 200% Leakage current ≤ predetermined value ± 200%	
寿命试验 Life Test	(105℃ 2000 小时试验后) (105 ° C for 2000 hours after the test)		容量变化 ≤ 初始测量值的 ± 20% 损耗值 ≤ 规定值的 ± 200% 漏电流 ≤ 初始规定值 Capacitance change ≤ ± 20% of the initial measured value Loss value ≤ predetermined value ± 200% Leakage current ≤ the initial specified value	



Electrical properties of the initial test (25 ± 3 °C) capacity, loss angle, leakage current test frequency: 100 or 120HZ

No.	1	2	3	4	5	6	7	8	9	10
C	21.2	21.5	20.9	20.6	21.1	21.0	20.8	21.3	20.4	21.6
DF%	4.5	5.1	4.6	5.1	5.3	4.8	4.7	4.3	4.5	4.0
I	11.5	12.6	12.6	13.5	12.8	14.0	13.2	13.0	13.4	15.1

发样：05