




材 质 及 电 镀	
塑 件:	PA66, UL94V-2
螺 丝:	M2.5、钢 镀锌
弹 片:	磷青铜、镀银
方 扣:	黄铜、环保
间 距:	5.08
电 气 性 能	
额定电压:	300V
额定电流:	10A
接触电阻:	20mΩ
绝缘电阻:	5000MΩ/1000V
耐电压:	AC1500V/Min
使用线径:	24-12AWG
机 械 性 能	
温度范围:	-40° C/105° C
瞬时温度:	250° C5秒
剥线长度:	6-7mm
扭力矩:	0.50N.m

极 数/P	2P	4P	8P	10P
对应长/L	10.16	20.32	40.64	50.80

	 慈溪科发电子有限公司 CIXI KEFA ELECTRONIC CO.,LTD
	NAME KF2EDGK--5.08



材 质 及 电 镀	
塑 件:	PA66, UL94V-2
螺 丝:	M2.5、钢 镀锌
弹 片:	磷青铜、镀银
方 扣:	黄铜、环保
间 距:	5.08
电 气 性 能	
额定电压:	300V
额定电流:	10A
接触电阻:	20mΩ
绝缘电阻:	5000MΩ/1000V
耐电压:	AC1500V/Min
使用线径:	24-12AWG
机 械 性 能	
温度范围:	-40° C/105° C
瞬时温度:	250° C5秒
剥线长度:	6-7mm
扭力矩:	0.50N.m

极 数/P	3P
对应长/L	15.24

	 慈溪科发电子有限公司 CIXI KEFA ELECTRONIC CO.,LTD
	NAME KF2EDGK--5.08(绿色)