

SSR SPECIFICATION



Name: Solid State Relay

Model: ZGT3-100DA

Manufacturer: XIQI Electrical Technology Co., Ltd.

Address: Fenghuang Industrial Zone Baishi Town
Wenzhou City

TEL: 0577-61723988 13373852285


Email: Jeffery@cnchog.com / Cecilia@cnchog.com

DATE: 2019-5-20

1. The standard of application:

With a switch no spark, no noise, high switching speed, anti-corrosion, moisture-proof, anti-vibration, long life, high reliability, electromagnetic compatibility and other characteristics. It can be widely used in aerospace, marine, household appliances, machine tools, telecommunications, automobile, mining, etc. automation and control area.



2. The Appearance of ZGT3-100DA:




3. The parameter of SSR-90DA:

Model	ZGT3-100DA
Control Voltage	3~32VDC
Min Control Current	5mA
Max Control Current	20mA
Load Voltage	24-480VAC
Load Current	100A
Insulation Resistance	1000M Ohm/ 500VDC
Off Leakage Current	<=8mA rms
On Voltage	<=1.5V
On-off Time	<=10ms
Ambient Temperature	-20~+75 ℃
Mounting Method	Screw fixed

4. The Wiring of ZGT-100DA:





5. The Heat sink of SSR-90DA:

During the use of SSR, it will give out a lot of heat, so in order to extend the life of your SSR.

